This Matrix Report is based on the Contract Circular Report										
Tender Number	**RT24-2013ME**									
Tender Description:	Supply and delivery of hospital ward and theatre furniture and ward requirements to the State									
Validity Expiring Date:	9/25/2013 11:00:00 AM									
Scenario Description:	Final Scenario									
Sorting Criteria:	Highest Points Awarded									
Item No	**Quantity Required**	**Description**								
RT24-01-001ME	See Quantity Awarded	Bowl Medical Stainless steel To comply to the latest issue of SANS 417, subsection 4 and 5.3, type A, size 4 Rim to conform to fig.1(a) of SANS 417 Stainless steel to comply with subsection 4.1.2 of SANS 417, proof of compliance must be submitted. Internal depth 45 mm Internal diameter at top 65 mm Each								
End User	**Response Fields**	**Duromed cc**								
As listed in Special Requirements and Conditions	**Responses**									
	Quantity Awarded - 1.0000	1								
	Delivered Price	11.4								
	Brand Name/Catalogue Number	United Poly								
	Delivery Period (Days)	90								
	Minimum order Quantities	5								
	Unit Of Measure	each								
	UOM Offered/Spec Deviation	0								
	Supplier Item Number	UPL 100-B								
	National Stock Number	18-033-3065 EA								
	Total Points	92								

Item No	Quantity Required	Description
RT24-01-002ME	See Quantity Awarded	Bowl Medical Stainless steel To comply to the latest issue of SANS 417, subsection 4 and 5.4, type B, size 2 Rim to conform to fig.1(a) of SANS 417 Stainless steel to comply with subsection 4.1.2 of SANS 417, proof of compliance must be submitted. Internal depth 60 mm Internal diameter at top 100 mm Each
End User	**Response Fields**	**Duromed cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	22.8
	Brand Name/Catalogue Number	United Poly
	Delivery Period (Days)	90
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UPL-103
	National Stock Number	18-970-1942 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-01-003ME	See Quantity Awarded	Bowl Medical Stainless steel To comply to the latest issue of SANS 417, subsection 4 and 5.4, type B, size 3 Rim to conform to fig.1(a) of SANS 417 Stainless steel to comply with subsection 4.1.2 of SANS 417, proof of compliance must be submitted. Internal depth 70 mm Internal diameter at top 150 mm Each
End User	**Response Fields**	**Duromed cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	53.01
	Brand Name/Catalogue Number	United Poly
	Delivery Period (Days)	90
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UPL-104
	National Stock Number	18-033-3005 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-01-004ME	See Quantity Awarded	Bowl Medical Stainless steel To comply to the latest issue of SANS 417, subsection 4 and 5.4, type B, size 4 Rim to conform to fig.1(a) of SANS 417 Stainless steel to comply with subsection 4.1.2 of SANS 417, proof of compliance must be submitted. Internal depth 90 mm Internal diameter at top 200 mm Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	125.4
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-055
	National Stock Number	18-970-1944 EA
	Total Points	100
Item No	**Quantity Required**	**Description**
RT24-01-005ME	See Quantity Awarded	Bowl stand To comply with the latest of CKS 157, type A Single Stainless steel, to comply with SANS 417, subsection 4.1.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**Hospital Equipment Manufacturers (Pty)Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	611
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-034A
	National Stock Number	18-970-1979 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-01-006ME	See Quantity Awarded	Dish Kidney Stainless steel To comply with the latest issue of SANS 417, subsection 4 and 5.2, type A, size 1 Rim to confirm to fig.1(d) of SANS 417 Stainless steel to comply with SANS 417, subsection 4.1.2, proof of compliance must be submitted. Overall length: 150 mm (±3 mm) Each
End User	**Response Fields**	**Duromed cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	22.8
	Brand Name/Catalogue Number	United Poly
	Delivery Period (Days)	90
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UPL-051
	National Stock Number	18-970-1907 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-01-007ME	See Quantity Awarded	Dish Kidney Stainless steel To comply with the latest issue of SANS 417, subsection 4 and 5.2, type A, size 2 Rim to confirm to fig.1(d) of SANS 417 Stainless steel to comply with SANS 417, subsection 4.1.2, proof of compliance must be submitted. Overall length: 195 mm (±3 mm) Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	41.3
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-060
	National Stock Number	18-970-1908 EA
	Total Points	96.8421

Item No	Quantity Required	Description
RT24-01-008ME	See Quantity Awarded	Dish Kidney Stainless steel To comply with the latest issue of SANS 417, subsection 4 and 5.2, type A, size 3 Rim to confirm to fig.1(d) of SANS 417 Stainless steel to comply with SANS 417, subsection 4.1.2, proof of compliance must be submitted. Overall length: 260 mm (±3 mm) Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	75.24
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-086
	National Stock Number	**18-970-1909 EA**
	Total Points	100
Item No	**Quantity Required**	**Description**
RT24-01-009ME	See Quantity Awarded	Jug Measure Plastic Graduated Dimensions and graduation markings must be equivalent to the latest issue of SANS 417, subsection 5.17 Material: Autoclavable durable plastic Capacity: 500 ml Each
End User	**Response Fields**	**Edge-Line Medical Products (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	26.35
	Brand Name/Catalogue Number	Sanjmed
	Delivery Period (Days)	30
	Minimum order Quantities	10
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	JUGPL500
	National Stock Number	18-097-0953 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-01-010ME	See Quantity Awarded	Jug Measure Plastic Graduated Dimensions and graduation markings must be equivalent to the latest issue of SANS 417, subsection 5.17 Material: Autoclavable durable plastic Capacity: 1000 ml Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	41.04
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-207
	National Stock Number	18-029-6964 EA
	Total Points	99.8682
Item No	**Quantity Required**	**Description**
RT24-01-011ME	See Quantity Awarded	Jug Measure Plastic Graduated Dimensions and graduation markings must be equivalent to the latest issue of SANS 417, subsection 5.17 Material: Autoclavable durable plastic Capacity: 2000 ml Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	77.52
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-399
	National Stock Number	18-009-5277 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-01-012ME	See Quantity Awarded	Jug Measure Graduated Dimensions and graduations markings must be equivalent to SANS 417, subsection 5.17 Stainless steel, to comply with the latest issue of SANS 417, subsection 4 and 5.17 Capacity: 500 ml Each
End User	**Response Fields**	**Duromed cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	79.8
	Brand Name/Catalogue Number	United Poly
	Delivery Period (Days)	90
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UPL-163
	National Stock Number	18-970-1873 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-01-013ME	See Quantity Awarded	Jug Measure Graduated Dimensions and graduations markings must be equivalent to SANS 417, subsection 5.17 Stainless steel, to comply with the latest issue of SANS 417, subsection 4 and 5.17 Capacity: 1000 ml Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	140.22
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-133
	National Stock Number	18-970-1874 (ea)
	Total Points	100

Item No	Quantity Required	Description
RT24-01-014ME	See Quantity Awarded	Jug Measure Graduated Dimensions and graduations markings must be equivalent to SANS 417, subsection 5.17 Stainless steel, to comply with the latest issue of SANS 417, subsection 4 and 5.17 Capacity: 2000 ml Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	246.24
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-254
	National Stock Number	18-008-3909 (EA)
	Total Points	100
Item No	**Quantity Required**	**Description**
RT24-02-001ME	See Quantity Awarded	Bed, hospital, two section To comply with the latest issue of SANS 521, in subsections 3.1 (a) and 5.1 (Type) of the latest issue of SANS 521 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors, two swivel , two locking Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Removable head and foot ends (ABS material is acceptable) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	5738
	Brand Name/Catalogue Number	Hartford
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-130
	National Stock Number	18-190-3272 (EA)
	Total Points	99

Item No	Quantity Required	Description
RT24-02-002ME	See Quantity Awarded	Bed, hospital, two section, complete with mattress To comply with the latest issue of SANS 521, in subsections 3.1 (a) and 5.1 (Type) of the latest issue of SANS 521 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors, two swivel , two locking Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Removable head and foot ends (ABS material is acceptable) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights

End User	Response Fields	Hospi-Furn (Pty) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	6911
	Brand Name/Catalogue Number	Hartford
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-130M
	National Stock Number	18-187-8239 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-02-003ME	See Quantity Awarded	Bed, hospital, two section with Trendelenberg To comply with the specifications in Appendix A, SEE ATTACHED. Note: where the item offered differs from the specification in Appendix A, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors, two swivel , two locking Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights d. Bedding support according to specification in Appendix A, subsection 3.14

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	6165
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-124
	National Stock Number	18-001-9077 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-02-004ME	See Quantity Awarded	Bed, hospital, two section with Trendelenberg, complete with mattress To comply with the specifications in Appendix A, SEE ATTACHED. Note: where the item offered differs from the specification in Appendix A, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors, two swivel , two locking Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights d. Bedding support according to specification

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	7050
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	40
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-124M
	National Stock Number	18-001-9068 (EA)
	Total Points	100

Item No	Quantity Required	Description
RT24-02-005ME	See Quantity Awarded	Bed, hospital high-low To comply with the latest issue of CKS 447 Note: where the item offered differs from the specification in CKS 447, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Hydraulically operated variable height operated by dual sided foot pedals Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors with a central castor locking system Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights d. Bedding support according to specification in Appendix A, subsection 3.14

End User	Response Fields	Arjo Huntleigh South Africa (Pty) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	10368.3
	Brand Name/Catalogue Number	ENTERPRISE
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	HMB-1002VC1ABAT
	National Stock Number	18-190-3451 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-02-006ME	See Quantity Awarded	Bed, hospital high-low, complete with mattress To comply with the latest issue of CKS 447 Note: where the item offered differs from the specification in CKS 447, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Bed must support a patient mass of 180 kg Hydraulically operated variable height operated by dual sided foot pedals Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors with a central castor locking system Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME The following accessories must be accommodated to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights d. Bedding support according to specification in Appendix A, subsection 3.14

End User	Response Fields	Arjo Huntleigh South Africa (Pty) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	11394.3
	Brand Name/Catalogue Number	ENTERPRISE
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each, (0% MATTRESS)
	Supplier Item Number	HMB-1002VC1ABATM1
	National Stock Number	18-001-9077 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-02-007ME	See Quantity Awarded	Bed, hospital intensive care, 4 section To comply with the latest issue of CKS 447 Note: where the item offered differs from the specification in CKS 447, except for the items specified below, the supplier must indicate the deviation and supply relevant details The mattress platform shall be in four sections allowing for a profiling action Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey The bed shall have a four section platform. The knee-break section adjustable via a manual mechanism Bed must support a patient mass of 180 kg Hydraulically operated variable height operated by dual sided foot pedals Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors with a central castor locking system Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details Oxygen cylinder holder Extension of bed must comply to CKS 447, subsection 3.5 The following accessories MUST be offered to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulleys and weights

End User	Response Fields	Hospi-Furn (Pty) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	15701
	Brand Name/Catalogue Number	Hartford
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-137
	National Stock Number	
	Total Points	96.9355

Item No	Quantity Required	Description
RT24-02-008ME	See Quantity Awarded	Bed, hospital intensive care, 4 section, complete with mattress To comply with the latest issue of CKS 447 Note: where the item offered differs from the specification in CKS 447, except for the items specified below, the supplier must indicate the deviation and supply relevant details The mattress platform shall be in four sections allowing for a profiling action Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey The bed shall have a four section platform. The knee-break section adjustable via a manual mechanism Bed must support a patient mass of 180 kg Hydraulically operated variable height operated by dual sided foot pedals Adjustable backrest with gas spring assist, suitable for 100 kg patient To be fitted with castors with a central castor locking system Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm Removable head and foot ends (ABS material may be offered) With collapsible safety sides, to comply with IEC 60601-2-52 Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME, but may have sections to accommodate mattress support angles Oxygen cylinder holder Extension of bed must comply to CKS 447, subsection 3.5 The following accessories MUST be offered to fit on the bed. The price for these accessories must not be included on this item bid price. a. Driprod b. Patient lifting pole with chain or strap and handle, must support a mass of 75 kg c. Traction pole with pulley
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	16818
	Brand Name/Catalogue Number	Hartford
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-137M
	National Stock Number	18-005-4303 EA
	Total Points	96.8281
Item No	**Quantity Required**	**Description**
RT24-02-009ME	See Quantity Awarded	Bed, hospital, obstetric, high-low, tilting, 2 section, complete with mattress Bed and fittings must accommodate various labour and delivery positions Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Mattress platform material Bed must support a patient mass of 180 kg Removable leg section Adjustable backrest with gas spring assist (0 to 60 degrees) with quick release. Controls at both sides of bed Hydraulically operated variable height operated by dual sided foot pedals Height range (mattress platform): 500 to 750 mm (approximately) Trendelenberg tilt, 12 degrees To be fitted with 125 mm castors with a central castor locking system Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm With collapsible safety sides, to comply with IEC 60601-2-52 Rubber buffer wheels at the corners of bed head end Mattress, two section, for body and foot sections, with cover. Body section must be suitable for all profile angles Mattress to comply with the latest issue of SANS 640 AND 1291-1 (type 2), except for thickness, as below, proof of compliance must be submitted. Mattress must support a patient of at least 180 kg and return to original shape when not in use To be constructed of flexible polyurethane foam complying with class 30, grade no.12 of SANS 640 Thickness: 150 mm (-0 and +5mm) Manufacturer must supply a 5 year warranty on the mattress Two lithotomy poles, height adjustable, swivel action, with leg support (not straps) Douche fitting Douche tray, stainless steel Drip ro
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	16205
	Brand Name/Catalogue Number	Hospi-Furn
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-046
	National Stock Number	18-007-0315 (ea)
	Total Points	99

Item No	Quantity Required	Description
RT24-02-010ME	See Quantity Awarded	Cot, adult, complete with mattress To comply with the latest issue SANS 521, subsection 5.4, fig. 5 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Length: 2 045 mm (± 12 mm) Width: 915 mm (± 6 mm) Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	4970
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-005
	National Stock Number	18-187-8248 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-02-011ME	See Quantity Awarded	Cot, adult, with rising backrest and Trendelenberg, with mattress To comply with the latest issue SANS 521, subsection 5.4, fig. 5 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Rising backrest support. Trendelenberg and anti-Trendelenberg positions Length: 2 045 mm (± 12 mm) Width: 915 mm (± 6 mm) Mattress support: mattress support other than weldmesh is required, provide details Mattress must comply with specifications in item RT24-02-014ME

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	6820
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	40
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-005T
	National Stock Number	18-187-8249 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-02-012ME	See Quantity Awarded	Cot, child, complete with mattress To comply with the latest issue SANS 521, subsection 5.4, fig. 5 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Mattress support: mattress support other than weldmesh is required, provide details Length: 1 370 mm (± 5 mm) Width: 760 mm (± 5 mm) Mattress must comply with specifications in item RT24-02-016ME

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3250
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-007
	National Stock Number	18-187-8251 EA
	Total Points	99.4708

Item No	Quantity Required	Description
RT24-02-013ME	See Quantity Awarded	Cot, child, with rising backrest and Trendelenberg, complete with mattress To comply with the latest issue SANS 521, subsection 5.4, fig. 5 Note: where the item offered differs from the specification in SANS 521, except for the items specified below, the supplier must indicate the deviation and supply relevant details Must comply with IEC 60601-2-52 (Particular requirements for basic safety and essential performance of medical beds) paragraphs: 201.1, 201.3, 201.7, 201.9, 201.13, 201.15, annex BB and annex CC Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Epoxy/nylon powder coating colours: white, cream or grey Rising backrest support Trendelenberg and anti-Trendelenberg positions Mattress support: mattress support other than weldmesh is required, provide details Length: 1 370 mm (± 5 mm) Width: 760 mm (± 5 mm) Mattress must comply with specifications in item RT24-02-016ME

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	5150
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-007T
	National Stock Number	18-187-8253 EA
	Total Points	100

Item No	Quantity Required	Description								
RT24-02-014ME	See Quantity Awarded	Mattress for hospital bed/cot To comply with the latest issue of SANS 640 AND 1291-1 (type 2), except for thickness indicated below. Proof of compliance must be submitted Must be compatible with items RT24-02-002ME, RT24-02-004ME, RT24-02-006ME, RT24-02-008ME, RT24-02-010ME and RT24-02-011ME The mattress with cover must be flexible to accommodate anatomical contouring of all the angles of the bed Mattress must support a patient of at least 180 kg and return to original shape when not in use Mattress must be radio-opaque. To be constructed of flexible polyurethane foam complying with class 30, grade no.12 of SANS 640 Overall dimensions: Length: 1 980 mm (-0 and +40mm) Width: 860 mm (-0 and +20mm) Thickness: 150 mm (-0 and +5mm) Must include removable cover according to RT24-02-015ME Manufacturer must supply a 2 year warranty on the mattress. The mattres must be made of memory foam material								
End User	**Response Fields**	**Arjo Huntleigh South Africa (Pty) Ltd**	**Hospital Equipment Manufacturers (Pty)Ltd**	**Hospi-Furn (Pty) Ltd**						
As listed in Special Requirements and Conditions	**Responses**									
	Quantity Awarded - 1.0000	0.3333	0.3333	0.3334						
	Delivered Price	946.2	1053	1119						
	Brand Name/Catalogue Number	DURAFOAM MATTRESS	Durafaom	Durafoam						
	Delivery Period (Days)	30	30	45						
	Minimum order Quantities	1	1	1						
	Unit Of Measure	each	each	each						
	UOM Offered/Spec Deviation	Each	0	n/a						
	Supplier Item Number	DUR 02	M-124	HF-100						
	National Stock Number	18-097-0677 EA								
	Total Points	92	89.8415	82.5637						
Item No	**Quantity Required**	**Description**								
RT24-02-015ME	See Quantity Awarded	Cover for mattress (for hospital bed/cot) To comply with the latest issue of SANS 1291-1, proof of compliance must be submitted Must be compatible with RT24-02-014ME Cover must be removable, water-resistant, air permeable material and radio-opaque Where a zip is incorporated it shall be: a heavy duty, large toothed synthetic zip to allow removal of the inner mattress totally covered by a flap extending over the zip to prevent ingress of fluids Manufacturer must supply a 2 year warranty on the cover								
End User	**Response Fields**	**Hospital Equipment Manufacturers (Pty)Ltd**	**Arjo Huntleigh South Africa (Pty) Ltd**	**Hospi-Furn (Pty) Ltd**						
As listed in Special Requirements and Conditions	**Responses**									
	Quantity Awarded - 1.0000	0.3333	0.3333	0.3334						
	Delivered Price	395	399	518						
	Brand Name/Catalogue Number	Durafaom	DURAFOAM MATTRESS COVER	Durafoam						
	Delivery Period (Days)	30	30	45						
	Minimum order Quantities	1	1	1						
	Unit Of Measure	each	each	each						
	UOM Offered/Spec Deviation	0	Each	n/a						
	Supplier Item Number	C-124	DUR 02 C	HF-101						
	National Stock Number	18-097-0685 EA								
	Total Points	100	91.0886	70.9747						

Item No	Quantity Required	Description
RT24-02-016ME	See Quantity Awarded	Mattress for child cot To comply with the latest issue of SANS 640 AND 1291-1 (type 2), proof of compliance must be submitted. Must be compatible with cot, child items RT24-02-008ME and RT24-02-009ME To be constructed of flexible polyurethane foam complying with class 30, grade no.12 of SANS 640 Overall dimensions: Length: 1 340 mm (-0 and + 30 mm) Width: 740 mm (-0 and + 20 mm) Thickness: 100 mm (-0 and + 5 mm) Must include cover according to RT24-02-013ME Manufacturer must supply a 2 year warranty on the mattress

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	625
	Brand Name/Catalogue Number	Durafaom
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	M-007
	National Stock Number	18-097-0741 EA
	Total Points	92.2929

Item No	Quantity Required	Description
RT24-02-017ME	See Quantity Awarded	Cover for mattress (child cot). To comply with the latest issue of SANS 1291-1 and proof of compliance must be submitted Must be compatible with mattress for child cot. Cover must be removable water-resistant, air permeable material and radio-opaque. Where a zip is incorporated it shall be: a heavy duty, large toothed synthetic zip to allow removal of the inner mattress. Must be totally covered by a flap extending over the zip to prevent ingress of fluids. Manufacturer must supply a 2 year warranty on the cover

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	345
	Brand Name/Catalogue Number	Durafaom
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	C-007
	National Stock Number	18-097-0685 EA
	Total Points	99.2105

Item No	Quantity Required	Description
RT24-02-018ME	See Quantity Awarded	Bassinet, hospital, type A, with stand complete with mattress To comply with the latest issue of CKS 237, type A Bassinet: durable, transparent plastic material Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Mattress: Must be in accordance with item RT24-02-021ME Items RT24-02-018ME to RT24-02-021ME shall be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1401
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	BAT 10
	National Stock Number	18-001-9146 EA
	Total Points	96.8289
Item No	**Quantity Required**	**Description**
RT24-02-019ME	See Quantity Awarded	Bassinet, hospital To comply with the latest issue of CKS 237, type A Type A: Durable, transparent plastic material. Items RT24-02-018ME to RT24-02-021ME shall be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	563
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	CRI 66
	National Stock Number	18-034-9643 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-02-020ME	See Quantity Awarded	Stand, (for bassinet) To comply with the latest issue of CKS 237. Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Must be compatible with items RT24-02-019ME Items RT24-02-018ME to RT24-02-021ME shall be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	685
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	ST 741
	National Stock Number	18-097-0572 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-02-021ME	See Quantity Awarded	Mattress, (for bassinet) To comply with the latest issue of SANS 640 and 1291-1 (see special conditions) To be constructed of flexible polyurethane foam complying with class 30, grade no. 12 of SANS 640 Thickness: 50 mm (-0 and + 5mm) Cover must be water-resistant, air permeable material Must be compatible with items RT24-02-019ME Items RT24-02-018ME to RT24-02-021ME shall be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	150
	Brand Name/Catalogue Number	Vita-NHM
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	MT 47
	National Stock Number	18-037-7067 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-02-023ME	See Quantity Awarded	Pressure relief mattress system with pump (200kg) Mattress shall support patients up to 200 kg. To comply with CKS 243. Bidder must indicate if their product complies. Insert either "Y" if your product fully complies with the specification or "N" if it does not comply. Use comment column to indicate how or why your product deviates from spec. A brochure with full technical specifications from manufacturer must be submitted. Please refer to the atached specification for RT24-02-023ME for more detailed specification.

End User	Response Fields	Arjo Huntleigh South Africa (Pty) Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	6840
	Brand Name/Catalogue Number	ALPHA ACTIVE4 MANUAL ADJ OF PRESSURE
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	648324/648311
	National Stock Number	18-189-8395 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-02-024ME	See Quantity Awarded	Examination couch To comply with the latest issue of CKS 243 Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Top cover to be available in a dark colour

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1400
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-088T
	National Stock Number	18-187-8258 EA
	Total Points	96.886

Item No	Quantity Required	Description
RT24-02-025ME	See Quantity Awarded	Examination couch, with tilting backrest To comply with the latest issue of CKS 243, but must have a tilting backrest Backrest must tilt up to 60° from horizontal and must be stable in at least 4 positions between 0° and 60° Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Top cover to be available in a dark colour
End User	**Response Fields**	**Arjo Huntleigh South Africa (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1438.68
	Brand Name/Catalogue Number	ARJO HUNTLEIGH EXAMINATION COUCH
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	COU27-2 SECTION
	National Stock Number	18-970-2618 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-03-001ME	See Quantity Awarded	Bedpan Slip-in, with handle Re-usable Autoclavable polypropelene Finishing must be smooth Size: Adult Length: 250 mm x 400 mm Height: 20 mm (Front) x 100mm (Back) Each
End User	**Response Fields**	**I SANDLER & Co cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	214.32
	Brand Name/Catalogue Number	Paramedic
	Delivery Period (Days)	30
	Minimum order Quantities	6
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Sugro 050
	National Stock Number	18-032-0678 EA
	Total Points	90

Item No	Quantity Required	Description
RT24-03-002ME	See Quantity Awarded	Bedpan To comply with the latest issue of SANS 417, subsection 4 and 5.8 Stainless steel, to comply with the latest issue of SANS 417, subsection 4.1.2. Proof of compliance must be submitted. Size: Adult Each
End User	**Response Fields**	**Bioclin Solutions cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	343.14
	Brand Name/Catalogue Number	Bioclin
	Delivery Period (Days)	42
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	None
	Supplier Item Number	Inst-067
	National Stock Number	18-970-1912 EA
	Total Points	98.1394
Item No	**Quantity Required**	**Description**
RT24-03-003ME	See Quantity Awarded	Bedpan and urinal stand To comply with the specifications in appendix M, figure 1 EXCEPTION: Instead of 3 pairs of urinal holders, 5 pairs are required, 180 mm apart Upper edges of tray must not be folded over Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	2600.5
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	UST 380
	National Stock Number	18-007-6730 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-03-004ME	See Quantity Awarded	Urinal, Male With lid Autoclavable Polypropelene Material: Made of plastic and equivalent to dimensions and type A or B of the latest issue of SANS 417, subsection 5.9 Volume: 1 000 ml Each
End User	**Response Fields**	**Duromed cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	26.22
	Brand Name/Catalogue Number	United Poly
	Delivery Period (Days)	90
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UPL-144
	National Stock Number	18-970-1998 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-03-005ME	See Quantity Awarded	Urinal To comply to the latest issue of SANS 417, subsection 4 and 5.9 Material: Stainless steel, type A or B, to comply with subsection 4.1.2 of SANS 417, proof of compliance must be submitted Volume: 1 000 ml Each
End User	**Response Fields**	**Ecomed Medical cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	346.66
	Brand Name/Catalogue Number	Ultra
	Delivery Period (Days)	56
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	each
	Supplier Item Number	2002-3005
	National Stock Number	18-970-1998 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-03-006ME	See Quantity Awarded	Urinal rack, wallmount. To hold 5 urinals, conforming to Fig. 9(b) of SANS 417) Urinals must hang at an angle to allow liquid to drip out. NO TRAY BELOW URINALS Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Proof of complinace must be submitted

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	550
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-098A
	National Stock Number	18-190-3765 EA
	Total Points	99.5064

Item No	Quantity Required	Description
RT24-04-001ME	See Quantity Awarded	Cabinet, anaesthetist`s, mobile. Front of cabinet to be divided in 2 sections. One section with 6 drawers and other section with 3 open shelves. All drawers to have a durable sliding mechanism with stop to prevent total extraction of drawer. Two drawers to have partitions. Approximate dimensions: Height: 1 100 mm Width: 460 mm Length: 1 000 mm. Top surface: stainless steel. Epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2. (See special conditions) Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Mounted on 4 heavy duty swivel castors 125 mm diameter, two swivel two braking. Castors shall be in accordance with SANS 621 (See Special Conditions). Castors must be antistatic. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. All surfaces, including welds, to be free from pits, scratches, crimps, folds, buckles and other defects.

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	5800
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-026C
	National Stock Number	18-190-4084 (EA)
	Total Points	100

Item No	Quantity Required	Description
RT24-04-002ME	See Quantity Awarded	Cabinet, medicine, mobile. To comply with the latest issue of CKS 556. Hinge other than "piano hinge" may be used. Folding or pull-out type writing shelf. The latter must have a stopper. Folding shelf (if supplied) to be on the left hand door. Cabinet must be lockable. Lock must not have an identification code displayed. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2. (See Special Conditions). Mounted on 4 heavy duty swivel castors 125 mm diameter, two swivel, two braking. Castors must be antistatic. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner. All surfaces, including welds, to be free from pits, scratches, crimps, folds, buckles and other defects.

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	3050.1
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	UDC 126
	National Stock Number	18-190-4085 (EA)
	Total Points	99

Item No	Quantity Required	Description
RT24-04-003ME	See Quantity Awarded	Cabinet, medicine, mobile (ABS plastic) Top surface to be flat, suitable for writting and dispensing Multiple drawers with dividers (4- 6 drawers) Two large storage drawers, no dividers Drawers must have smooth, durable sliding mechanism with stop to prevent total extraction of drawer Appriximate dimensions: Height: 950 mm Width: 750 mm Depth: 500 mm Mounted on 4 heavy duty swivel castors 125 mm diameter, two swivel and two braking. Castors must comply wih SANS 621 and proof of compliance must be submitted. Castors must be antistatic. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Each

End User	Response Fields	Siyakhanda Medical Services (Pty) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	7646.42
	Brand Name/Catalogue Number	Bailida MX34 PRo
	Delivery Period (Days)	70
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	MX 34 PRO
	National Stock Number	18-187-8264 EA
	Total Points	96.5356

Item No	Quantity Required	Description
RT24-04-004ME	See Quantity Awarded	Cabinet, poison/drug wall type Size: SMALL To comply with the latest issue of CKS 181 (fig 2), type B Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, Proof of compliance must be submitted. The mild steel plate shall have a nominal thickness of not less than 1,20 mm NOTE: The cabinet must not be marked "Poison" Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	715
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-045S
	National Stock Number	18-007-6033 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-04-005ME	See Quantity Awarded	Cabinet, poison/drug wall type Size: LARGE To comply with the latest issue of CKS 181 (fig 4), type D Double door type with internal cupboard. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. The mild steel plate shall have a nominal thickness of not less than 1,20 mm NOTE: The cabinet must not be marked "Poison" Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1690
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-045B
	National Stock Number	18-185-2315 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-04-006ME	See Quantity Awarded	Cabine trolley, sterile pack, mobile To be in accordance Annexure G attached, drawing ME 00.30.45. The cabinet shall be constructed of 1,2 mm thick mild steel sheet and shall be mounted on, and attached to a 32 mm x 32 mm x 5 mm inverted angle iron base The corners of the base shall be fitted with gussets to provide additional support for the mild steel tubular legs with 32 mm outside diameter x 1,6 mm thickness The cabinet shall be provided with two adjustable mild steel shelves of rigid construction The doors shall be flush fitting, suspended on chromium-plated butt hinges and designed to open 180°. The doors shall be of rigid construction and reinforced internally by 1,2 mm thick vertical channel members. The ends of the reinforcing members shall be sealed The design of the doors shall be such that the door fitted with the locking bars shall also lock the adjacent door Mounted on 4 heavy duty swivel castors 125 mm diameter, two swivel and two braking. Castors must comply wih SANS 621 and proof of compliance must be submitted. Castors must be antistatic. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted Each

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	2750
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	ST 96
	National Stock Number	18-003-3495 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-04-007ME	See Quantity Awarded	Cabinet, utility, mobile To be in accordance with Annexure H, as per drawing ME00.30.35, see attached. Material: Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, Proof of compliance must be submitted. Shall be constructed of 1,2mm thick mild steel sheet The cabinet must be fitted with two pull out or swivel drawers, one on either side which must comply with SANS 343, par. 3.3.4 All drawers must have a durable sliding mechanism with stop to prevent total extraction of drawer. The four doors of the top compartment must be fitted with a door stopper mechanism (hard rubber and sunk in screws). The doors must be fitted with durable hinges The retractable worktop shall be constructed of 1,2 mm thick stainless steel. Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2. proof of compliance must be submitted The worksop must be of rigid construction and capable of being extended (not less than 300 mm) beyond the face of the cabinet without canting Mounted on 4 heavy duty swivel castors 125 mm diameter, two swivel and two braking Castors: must comply with the latest issue SANS 621, proof of compliance must be submitted. Castors must be antistic Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	7316
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-108
	National Stock Number	18-007-6023 EA
	Total Points	99.0804

Item No	Quantity Required	Description
RT24-06-001ME	See Quantity Awarded	Restraint system, wrist bands Padded bands System to secure patient's hands to the bed frame System to be secure, safe and tamperproof. Locking mechanism to prevent unauthorised opening. Size: Three sizes must be provided to accomodate patients of different sizes
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1300
	Brand Name/Catalogue Number	MEDICARE SV3251-SVF3252-SVF3253
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1) Pair
	Supplier Item Number	SV3251-SVF3252-SVF3253
	National Stock Number	
	Total Points	95
Item No	**Quantity Required**	**Description**
RT24-06-002ME	See Quantity Awarded	Restraint system, ankle bands. System to secure patient's ankles to bed frame. System to be secure, safe and tamperproof. Locking mechanism to prevent unauthorised opening of belt Size: Three sizes must be provided to accomodate patients of different sizes
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1685
	Brand Name/Catalogue Number	MEDICARE SV3351-SVF3350-SVF3352-SVF3353
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1) Pair
	Supplier Item Number	SV3351-SVF3350-SVF3352-SVF3353
	National Stock Number	18-187-0740 EA (S) 18-185-2639 EA (M) 18-185-2636 EA (L)
	Total Points	95

Item No	Quantity Required	Description
RT24-06-003ME	See Quantity Awarded	Restraint system, waist belt. System to prevent patient from getting out of bed. System to be secure, safe and tamperproof. Must allow patient to turn to either side and sit without the risk of falling. Locking mechanism to prevent unauthorised opening of belt Size: Three sizes must be provided to accomodate patients of different sizes

End User	Response Fields	Sanbonani Holdings (PTY) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	2500
	Brand Name/Catalogue Number	MEDICARE SVF3001-SV3000-SVF3002-SVF3003
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	SVF3001-SV3000-SVF3002-SVF3003
	National Stock Number	18-016-3373 EA (S) 18-016-3377 EA (M) 18-007-6141 EA (L)
	Total Points	95

Item No	Quantity Required	Description
RT24-07-001ME	See Quantity Awarded	Locker, bedside, mild steel To comply with the latest issue of SANS 343, Type 1 Material: Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2 Must have a rail on both sides Pull-out drawer Locker mounted on 4 castors. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Drawer must have a durable sliding mechanism and stop to prevent total extraction of drawer. Materials which are easily cleaned and of lasting finish, and low noise generating nature, must be used. Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1645
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-028
	National Stock Number	18-003-7829 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-07-002ME	See Quantity Awarded	Locker, bedside, ABS plastic To comply with the latest issue of SANS 343, Type 1, with the following exception: Material: ABS or similar sturdy, durable material Must have a rail on both sides Pull-out drawer Locker mounted on 4 castors. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Each

End User	Response Fields	Sanbonani Holdings (PTY) Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1250
	Brand Name/Catalogue Number	HOPEFULL Z01
	Delivery Period (Days)	75
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	HF-Z01
	National Stock Number	18-187-8266 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-07-003ME	See Quantity Awarded	Overbed table, cantilever type Adjustable height To comply with the latest issue of SANS 777, Type B Mild steel frame with epoxy powder-coated or nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted Bonded wood melamine resin surface table-top with aluminium or similar edging Height adjustment from ± 740 mm to 1 090 mm Automatic lock Height must be adjustable by patient Each

End User	Response Fields	Class Three Medical Solution
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1485.57
	Brand Name/Catalogue Number	Edrich Engineering
	Delivery Period (Days)	21
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	OE 22D
	National Stock Number	18-011-1798 EA
	Total Points	98

Item No	Quantity Required	Description
RT24-07-004ME	See Quantity Awarded	Overbed table, cantilever type Adjustable height To comply to the latest issue of SANS 777, Type B Material: Mild steel frame and table top with epoxy/nylon powder-coated finish to comply with the latest issue of SANS 778 paragraph 5.2, proof of compliance must be submitted. OR Alternative material: ABS plastic Height adjustable from ± 740 mm to 1090 mm Automatic lock Height must be adjustable by patient Each

End User	Response Fields	Sanbonani Holdings (PTY) Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1460
	Brand Name/Catalogue Number	HOPEFULL MO1
	Delivery Period (Days)	75
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	HF-M01
	National Stock Number	18-187-8268 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-07-006ME	See Quantity Awarded	Table, utility To comply with the specifications in Appendix P, Type B, see attached. Stainless steel table-top, without bottom shelf Stainless steel must comply wit the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Rounded edges and corners Size: ± 1 720 mm x ±810 mm Height: 900 mm Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	4805
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-056A
	National Stock Number	18-034-9650 EA
	Total Points	100

Item No	Quantity Required	Description

RT24-08-001ME	See Quantity Awarded	Scale, weighing electronic, baby and child convertible. Battery operated Automatic switch off Weighing capacity up to 20 kg Increments: 10g up to 10kg, 20g > 10kg LCD display: digits at least 20 mm high Electronic damper Hold feature to retain weight reading Function to display breast milk intake Each Items RT24-08-001ME and RT24-08-002ME shall be considered as a series								
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**								
As listed in Special Requirements and Conditions	**Responses**									
	Quantity Awarded - 1.0000	1								
	Delivered Price	844.74								
	Brand Name/Catalogue Number	NAGATA BW-2010								
	Delivery Period (Days)	60								
	Minimum order Quantities	1								
	Unit Of Measure	each								
	UOM Offered/Spec Deviation	One(1)								
	Supplier Item Number	BW-2010								
	National Stock Number	18-007-6698 EA								
	Total Points	95								
Item No	**Quantity Required**	**Description**								
RT24-08-002ME	See Quantity Awarded	Scale, carry case Must be of durable nylon with zipper and carrying strap Must be compatible with item no RT24-08-001ME. Each Items RT24-08-001ME and RT24-08-002ME shall be considered as a series.								
End User	**Response Fields**	**Ecomed Medical cc**								
As listed in Special Requirements and Conditions	**Responses**									
	Quantity Awarded - 1.0000	1								
	Delivered Price	141.23								
	Brand Name/Catalogue Number	Ultra								
	Delivery Period (Days)	56								
	Minimum order Quantities	3								
	Unit Of Measure	each								
	UOM Offered/Spec Deviation	each								
	Supplier Item Number	2002-8002								
	National Stock Number	18-097-0976 EA								
	Total Points	92								

Item No	Quantity Required	Description
RT24-08-003ME	See Quantity Awarded	Scale, analog/mechanical, bathroom type Weighing capacity: 0 - 150 kg at least Large dial display Spring lever mechanism with vanadium steel spring Heavy, hardened steel pivots and bearing Scale must be of robust construnction Each
End User	**Response Fields**	**Ecomed Medical cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	314.24
	Brand Name/Catalogue Number	Ultra
	Delivery Period (Days)	56
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	each
	Supplier Item Number	2002-8003
	National Stock Number	18-970-5508 EA
	Total Points	92
Item No	**Quantity Required**	**Description**
RT24-08-004ME	See Quantity Awarded	Scale, electronic, bathroom type To comply with the specifications on Appendix H, Type 3, see attached Capacity: at least 200 kg Battery operated Large LCD display with hold function Automatic switch-off Mother/child function to determine mass of a child held by an adult Scale must be of robust construction Each
End User	**Response Fields**	**Delta Surgical S.A (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3267.97
	Brand Name/Catalogue Number	SECA 874 Flat Scale Electronic
	Delivery Period (Days)	84
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	SE 874
	National Stock Number	18-185-2322 EA
	Total Points	98

Item No	Quantity Required	Description
RT24-08-005ME	See Quantity Awarded	Scale, with large dial To comply with the specifications on Appendix H, Type 2, see attached. Capacity: at least 150kg Dial to be at least 150 mm in diameter Must include height measuring rod Mounted on castors, roller size: 30 - 50 mm Fixed direction Scale to be able to tilt for moving Each
End User	**Response Fields**	**Delta Surgical S.A (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3340.59
	Brand Name/Catalogue Number	SECA 786 with Height Rod
	Delivery Period (Days)	84
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	SE 786
	National Stock Number	18-097-0981 EA
	Total Points	98
Item No	**Quantity Required**	**Description**
RT24-08-006ME	See Quantity Awarded	Scale, electronic, neonatal Battery operated Weighing capacity up to 20 kg Increments: 0 - 10 kg x 5 g, 10 - 20 kg x 10 g Electronic damper Hold feature to retain weight reading Function to display breast milk intake Each
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	2326.74
	Brand Name/Catalogue Number	NAGATA BW-20
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	BW-20
	National Stock Number	18-181-2703 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-08-010ME	See Quantity Awarded	Length board To measure length of children under 23 months, lying down Range: 20 - 125 cm, graduated in m, cm and mm, with numbers at metre and cm positions Measuring surface must be free of all moving parts that may affect the markings Fixed headboard, rigidly attached at 90° to horizontal surface Headboard to be at least 15 cm wide and at least 15 cm high Zero position at headboard, length reading made by movable footboard Movable footboard must slide easily on the horizontal section and lock in the measurement position Footboard must lock at 90° to the horizontal measuring section Locking mechanism must not affect the measuring surface Must be made of durable, non-flexible, smooth material that is water resistant, easy to clean, with no sharp edges or unfinished parts

End User	Response Fields	Ecomed Medical cc
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	724.57
	Brand Name/Catalogue Number	Ultra
	Delivery Period (Days)	56
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	each
	Supplier Item Number	2002-8010
	National Stock Number	
	Total Points	92

Item No	Quantity Required	Description
RT24-09-001ME	See Quantity Awarded	Transfer board, 80 cm Complete with disposable cover Size: 80 cm x 50 cm (± 20 mm) Radiotransluscent With handles Items RT24-09-001ME to RT24-09-002ME shall be considered as a series

End User	Response Fields	Sanbonani Holdings (PTY) Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	2000
	Brand Name/Catalogue Number	MEDIROLLER TMR 6220
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMR 6220
	National Stock Number	18-014-8397 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-09-002ME	See Quantity Awarded	Transfer board cover, 80 cm Durable disposable plastic cover To fit transfer board size: 80 cm x 50 cm (± 20 mm) Must be compatible with transfer board on item RT24-09-001ME Items RT24-09-001ME to RT24-09-002ME shall be considered as a series Each
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1300
	Brand Name/Catalogue Number	MEDICARE TMR 6270
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMR 6270
	National Stock Number	18-097-1028 EA
	Total Points	95
Item No	**Quantity Required**	**Description**
RT24-09-003ME	See Quantity Awarded	Transfer board, 180 cm Complete with disposable cover Size: 180 cm x 50 cm (± 20 mm) Radiotransluscent With handles Items RT24-09-003ME to RT24-09-004ME shall be considered as a series
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3450
	Brand Name/Catalogue Number	MEDI-ROLLER TMR 6200
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMR 6200
	National Stock Number	18-097-1025 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-09-004ME	See Quantity Awarded	Transfer board cover, 180 cm Durable disposable plastic cover To fit transfer board size: 180 cm x 50 cm (± 20 mm) Must be compatible with transfer board on item RT24-09-003ME Items RT24-09-003ME to RT24-09-004ME shall be considered as a series
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1300
	Brand Name/Catalogue Number	MEDICARE TMR 6270
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMR 6270
	National Stock Number	18-097-1034 EA
	Total Points	95
Item No	**Quantity Required**	**Description**
RT24-09-005ME	See Quantity Awarded	Transfer sheet/system Complete with disposable cover Size: 180 cm x 70 cm (± 20 mm) Radiotransluscent With handles With roll mat Folding Items RT24-09-005ME to RT24-09-006ME shall be considered as a series
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3450
	Brand Name/Catalogue Number	MEDI-SLIDE TMS-6340
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMS-6340
	National Stock Number	18-097-1021 EA
	Total Points	95

Item No	Quantity Required	Description
RT24-09-006ME	See Quantity Awarded	Transfer sheet/system cover Durable disposable plastic cover To fit transfer sheet/system size: 180 cm x 70 cm (± 20 mm) Must be compatible with transfer sheet/system (RT24-09-005ME) Items RT24-09-005ME to RT24-09-006ME shall be considered as a series
End User	**Response Fields**	**Sanbonani Holdings (PTY) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1300
	Brand Name/Catalogue Number	MEDICARE TMR 6270
	Delivery Period (Days)	60
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	One(1)
	Supplier Item Number	TMR 6270
	National Stock Number	18-097-1034 EA
	Total Points	95
Item No	**Quantity Required**	**Description**
RT24-10-001ME	See Quantity Awarded	Drip stand, mobile To comply with the latest issue of CKS 179, Type A Mild steel frame with epoxy powder-coated or nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Drag chain to be supplied on purchaser request Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	463
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	DT 41
	National Stock Number	18-970-7500 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-10-002ME	See Quantity Awarded	Dripstand, mobile To comply with the latest issue of CKS 179, Type C Stainless steel, to comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted. Drip stand, mobile To comply with the latest issue of CKS 179, Type A Mild steel frame with epoxy powder-coated or nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Drag chain to be supplied on purchaser request

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	808.1
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	DTSS 5
	National Stock Number	18-024-2267 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-10-003ME	See Quantity Awarded	Kick-about, for bucket To comply with the specification on Appendix G, Type A, see attached. Stainless steel, with medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable The horizontal braces to be arranged in a flat cross formation. Item RT24-10-003ME and RT24-10-004ME will be considered as a series

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	252
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	KK 21
	National Stock Number	18-007-6186 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-10-004ME	See Quantity Awarded	Bucket for kick-about, To comply with the latest issue of SANS 417, subsection 4 and 5.18, Type A Material: stainless steel, to comply with the latest issue of 417, subsection 4.1.2, proof of compliance must be submitted Capacity: 14 litre. With standing hoop. Rim of the bucket must to comply with SANS 417, fig 1(a) Must be compatible with kick-about, Type A. (item RT24-10-003ME) Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	360.12
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	BT 021
	National Stock Number	18-187-8273 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-10-005ME	See Quantity Awarded	Kick-about, for basin To comply with the specifications in Appendix G, Type B Must be compatible with item RT24-10-006ME Stainless steel, with mediumdirectional satin finish. Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Mounted on four legs fitted with castors. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Item RT24-10-005ME and RT24-10-006ME must be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	291
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	KT 027
	National Stock Number	18-097-0858 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-10-006ME	See Quantity Awarded	Kick about basin To comply with with the latest issue of SANS 417, subsections 4 and 5.19, Size 1 Material Stainless steel, to comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted. Must be compatible with item RT24-10-005ME Top inner diameter: 330 mm (± 6 mm) Height: 150 mm (± 6 mm) Bottom inner diameter: 220 mm (± 6 mm) Rim of the flange must conform with fig 1(d) of SANS 417. Bottom of the basin must be slightly recessed upward to ensure stability and there must be a flat between the recess and sides of the basin. Each Item RT24-10-005ME and RT24-10-006ME will be considered as a series

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	190
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	BW 5
	National Stock Number	18-097-0844 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-11-002ME	See Quantity Awarded	Stool, anaesthetist, with castors To comply with the specification in Appendix J, Type B, see attached. Aluminium flat seat Height adjustments, floor to top of seat: 485 mm to 685 mm Spindle to be screwedwith square thread Castors: 75 mm Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1699
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-078A
	National Stock Number	18-007-6754 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-11-003ME	See Quantity Awarded	Stool, foot, double step To comply with the specification as per drawing ME 00.30.38, see attached. Aluminium chequered plate top Stainless steel edging Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	700
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	DFS 6
	National Stock Number	18-003-6107 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-11-005ME	See Quantity Awarded	Stool, foot, single step To comply with the specification as per drawing ME 00.30.38, see attached. Aluminium chequered plate top Stainless steel edging Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	355.9
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	SFS 1
	National Stock Number	18-003-6113 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-11-006ME	See Quantity Awarded	Stool, foot, single step To comply with the specification as per drawing ME 00.30.38, see attached. Rubber top and stainless steel edging Rounded corners and no sharp edges Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	490.21
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	SFS 29
	National Stock Number	18-007-6066 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-11-007ME	See Quantity Awarded	Stool, visitor, hospital, To comply with the specification in Appendix K, see attached. Seat length: 900mm Seat width: 305mm Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Hardwood top with natural finish
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	395
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	VTS 75
	National Stock Number	18-007-6772 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-11-008ME	See Quantity Awarded	Stool, bathroom To comply with the specification in Appendix K, see attached. Seat length: 450 mm Seat width: 305 mm Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Hardwood top with natural finish

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	354
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-079
	National Stock Number	18-007-6755 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-11-009ME	See Quantity Awarded	Screen, bedside, wheeled Complete with curtain With four panels To comply with the latest issue of SANS 897, fig.3, Type C Overall height 1 680 mm Mild steel frame and legs with epoxy/nylon powder-coated finish, to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Castors: 75 mm Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Plastic curtains hinges and curtain hooks should be placed in such a way that there is no opening on the sides of curtains and between panels Curtain to be as follows: Strong non-transparent plastic Sides to be strengthened and to be full fit in frame sections. Curtain must be easily removable Each

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1585.1
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	SC 441
	National Stock Number	18-024-2234 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-11-010ME	See Quantity Awarded	Screen, curtain, bedside a Strong non-transparent plastic Sides to be strengthened Strong non-transparent Sides to be strengthened and curtains to be full fit in frame sections Must be compitable with item RT24-11-009ME Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	198
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	SC 440
	National Stock Number	18-097-0992 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-11-011ME	See Quantity Awarded	Stool, anaesthetist, with backrest To comply with the specification in Appendix J, Type C, see attached. Height adjustment, floor to top of seat: 485 mm to 685 mm Castors: 75 mm Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each
End User	**Response Fields**	**Nomageba Medical cc**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	2023.16
	Brand Name/Catalogue Number	Edge Line
	Delivery Period (Days)	30
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	EL25
	National Stock Number	18-188-5285 EA
	Total Points	95.1377

Item No	Quantity Required	Description
RT24-12-001ME	See Quantity Awarded	Trolley, emergency, crash cart, mordern type Please see attached specification for more detailed specification (RT24-12-001ME)
End User	**Response Fields**	**Siyakhanda Medical Services (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	12871.72
	Brand Name/Catalogue Number	Bailida MX 34 EMG
	Delivery Period (Days)	70
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	MX34 EMG
	National Stock Number	18-185-2407 EA
	Total Points	98
Item No	**Quantity Required**	**Description**
RT24-12-002ME	See Quantity Awarded	Trolley, gas cylinder, for 180 mm diameter cylinder To comply with the latest issue of SANS 895 Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	715
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	GT 056
	National Stock Number	18-007-7661 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-003ME	See Quantity Awarded	Gas cylinder trolly, for 300 mm diameter cylinder To comply with the latest issue of SANS 895, with the following exception: To accommodate gas cylinder: Diameter of cylinder: 300 mm Length of cylinder: 1 300 mm Material: Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	772
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	CT 057
	National Stock Number	18-097-1039 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-12-004ME	See Quantity Awarded	Trolley, gas cylinder, upright type Base diameter: 540 mm Overall height: 670 mm Material: Mild steel frame with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, proof of compliance must be submitted. Mounted on 4 x 75 mm swivel castors Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	485
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	GST 54
	National Stock Number	18-177-3416 EA
	Total Points	98.2516

Item No	Quantity Required	Description
RT24-12-005ME	See Quantity Awarded	Trolley, anaesthetist. Type 3 , size C. To comply with the latest issue of SANS 726 (see fig 2 and table 2). Size: Length: 455 mm (± 5 mm). Width: 455 mm (± 5 mm). The upper part is enclosed to contain a drawer (with no divisions) opening to the front. Drawer must have a stopper to prevent complete removal of drawer. Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves. The top shelf has a rail along sides and back. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Stainless steel throughout. Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Four swivel castors with a diameter of 75 mm each. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner.

End User	Response Fields	Nomageba Medical cc
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	2661.25
	Brand Name/Catalogue Number	Edgeline
	Delivery Period (Days)	30
	Minimum order Quantities	5
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	EL 5955
	National Stock Number	18-034-9653 EA
	Total Points	95.4455

Item No	Quantity Required	Description
RT24-12-006ME	See Quantity Awarded	Anaesthetist trolley To comply with the latest issue of SANS 726, Size C, Type 5 (see fig. 5 and table 2) Size: Length: 455mm (± 5mm) Width: 455 mm (± 5 mm) The upper part is enclosed to contain a drawer (with no divisions) opening to the front. Drawer must have a stopper to prevent complete removal of drawer Durable rubber plugs (or similiar noise reducing material) must be insertedinto rails below removable shelves The top shelf must not have rail and the bottom shelf must have a continuos rail on all four sides Material: Stainless steel through out Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Materials which are easily cleaned and of lasting finish, and low noise generating nature, must be used. Mounted on 4 x 75 mm swivel castors Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	2095
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-055A
	National Stock Number	18-007-7694 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-12-008ME	See Quantity Awarded	Trolley, medical dressing. Type 4, size A. To comply with the latest issue of SANS 726 (see fig 4). Length: 915 mm (± 5 mm). Width: 455 mm (± 5 mm). The trolley is open and has two removable stainless steel shelves. Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves. It has a continuous guard rail along the sides and back of the top shelf and a continuous rail fitted around the bottom, above the bottom shelf. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Stainless steel throughout. Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Four swivel castors with a diameter of 75 mm each. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner.

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1600
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	DT 915
	National Stock Number	18-007-7676 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-009ME	See Quantity Awarded	Trolley, medical dressing. Type 4, size C. To comply with the latest issue of SANS 726 (see fig 4). Length: 455 mm (± 5mm). Width: 455 mm (± 5 mm). The trolley is open and has two removable stainless steel shelves. Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves. It has a continuous guard rail along the sides and back of the top shelf and a continuous rail fitted around the bottom, above the bottom shelf. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2. (See Special Conditions). Shelves to be of stainless steel. Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Four swivel castors with a diameter of 75 mm each. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner.

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	980
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-053I
	National Stock Number	18-007-7675 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-12-010ME	See Quantity Awarded	Trolley, medical dressing with bucket and bowl attachment. Type 6. To comply with the latest issue of SANS 726 (see fig 6). The trolley is open and has two removable stainless steel shelves. Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves. It has a continuous top guard rail around the four sides. No guard rail on the bottom shelf. Bowl attachment (upper bracket) to accommodate a bowl (size 3) as per paragraphs 4 and 5.21 of SANS 417. Bucket attachment (lower bracket) to accommodate a 14 litre bucket as per paragraphs 4 and 5.18 of SANS 417. Trolley to be supplied with a bucket and bowl as specified. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2. (See Special Conditions). Proof of compliance must be submitted. Shelves to be of stainless steel. Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions), of compliance must be submitted. Four swivel castors with a diameter of 75 mm each. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner.

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	2221.5
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	BBT
	National Stock Number	18-007-7703 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-011ME	See Quantity Awarded	Trolley, medical instrument To comply with the latest issue of SANS 726, Type 2, size A Length: 915 mm (± 5 mm) Width: 455 mm (± 5 mm) Stainless steel with medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted The trolley is open and has two removable stainless steel shelves Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves It has no guard rail around the top and a continuous rail fitted around the bottom, above the bottom shelf Four swivel castors with a diameter of 75 mm each. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35 mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1332
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-058I
	National Stock Number	18-177-3422 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-12-012ME	See Quantity Awarded	Trolley, medical instrument To comply with the latest issue of SANS 726, Type 2, Size A, Length: 915 mm (± 5 mm) Width: 455 mm (± 5 mm) The trolley is open and has two removable stainless steel shelves. Durable rubber plugs (or similiar noise reducing material) must be inserted into rails below removable shelves Must not have guard rail around the top and no guard rail on bottom, above shelf Stainless steel with medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Materials which are easily cleaned and of lasting finish, and low noise generating nature, must be used. Four swivel castors with a diameter of 75 mm each. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35 mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1178
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-058E
	National Stock Number	18-007-7685 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-12-013ME	See Quantity Awarded	Trolley, medical instrument To comply with the latest issue of SANS 726, Type 2, Size B, Length: 610 mm (± 5 mm) Width: 455 mm (± 5 mm) The trolley is open and has two removable stainless steel shelves. Durable rubber plugs (or similiar noise reducing material) must be inserted into rails below removable shelves Must not have guard rail around the top and no guard rail on bottom, above shelf Stainless steel with medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Materials which are easily cleaned and of lasting finish, and low noise generating nature, must be used. Four swivel castors with a diameter of 75 mm each. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35 mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	Hospital Equipment Manufacturers (Pty)Ltd
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	995
	Brand Name/Catalogue Number	Hospequip
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	H-058D
	National Stock Number	18-007-7691 EA
	Total Points	100

Item No	Quantity Required	Description
RT24-12-014ME	See Quantity Awarded	To comply with the latest issue of SANS 726, Type 2, size B Stainless steel medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Length: 610 mm (± 5 mm) Width: 455 mm (± 5 mm) The trolley is open and has two removable stainless steel shelves Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves No guard rail around the top but must have a continuous rail fitted around the bottom, above the shelf It has no guard rail around the top and a continuous rail fitted around the bottom, above the bottom shelf Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Four swivel castors with a diameter of 75 mm each. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35 mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1025
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	ITS 610
	National Stock Number	18-177-3425 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-015ME	See Quantity Awarded	Trolley, medical instrument To comply with the latest issue of SANS 726, Type 2, Size C (see figure 1 and table 1) Length: 455 mm (± 5 mm) Width: 455 mm (± 5 mm) The trolley is open and has two removable stainless steel shelves Durable rubber plugs (or similar noise reducing material) must be inserted into rails below removable shelves. Must not have guard rail around the top and no guard rail on bottom, above shelf Stainless steel with medium directional satin finish Stainless steel must comply with the latest issue of SANS 417, subsection 4.1.2, proof of compliance must be submitted Material: stainless steel medium directional satin finish. Materials which are easily cleaned and of lasting finish, and low noise generating nature, shall be used. Four swivel castors with a diameter of 75 mm each. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35 mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	865
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	IT 455
	National Stock Number	18-007-7694 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-016ME	See Quantity Awarded	Trolley, mortuary for hospital use Stainless steel body tray To comply with the latest issue of CKS 336 Complete with canopy frame With the following EXCEPTION: Canopy cover to be made of laminated PVC (not canvas) Material: stainless steel, grade A or B. Materials which are easily cleaned and of lasting finish, and low noise generating nature, must be used. Length: 2000 mm To be fitted with body straps Peripheral bumper guard and buffer wheels required Items RT24-18-016ME and RT24-18-017ME will be considered as a series Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	6475.2
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	MT 4
	National Stock Number	18-033-3991 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-12-017ME	See Quantity Awarded	Trolley, mortuary, cover To comply with the latest issue of CKS 336, subsection 4.5 Exception: Canopy cover to be made of laminated PVC (not canvas) Must be compatible with item RT24-12-016ME Items RT24-18-016ME and RT24-18-017ME will be considered as a series Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	1332
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	MTC 4
	National Stock Number	18-016-3623 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-018ME	See Quantity Awarded	Trolley, patient, with mattress. To comply with the latest issue of SANS 778. Type A (fig 1). Must support a patient of 180Kg mass With adjustable backrest. With collapsible safety sides. Overall length of stretcher top: 2 060 mm (± 5 mm). Stainless steel top with a medium directional satin finish. Stainless steel must comply with subsection 4.1.2 of the latest issue of SANS 417 (See special conditions). Proof of compliance must be submitted. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2. (See Special Conditions). Proof of compliance must be submitted. Two hooks on the drip rod. Oxygen cylinder holder. Mounted on 4 heavy duty locking, swivel castors 125 mm diameter, two swivel, two braking. Castors must be antistatic. Castors shall be in accordance with SANS 621 (see Special Conditions). Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: i) Solid plug (long) complying with SANS 621 subsection 3.5.6 or ii) Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner. Mattress: Must comply with item RT24-12-019ME. Items RT24-12-018ME, RT24-12-019ME and RT24-12-020ME will be considered as a series

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	6250
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	PT 6
	National Stock Number	18-033-3993 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-019ME	See Quantity Awarded	Mattress, for patient trolley To comply with the latest issue of SANS 640 and SANS 1291-1, Proof of compliance must be submitted To be constructed of flexible polyurethane foam, to comply with SANS 640, Grade no. 12, Class 30. Proof of compliance must be submitted Covered with waterproof non-slip removable cover as specified in item RT24-12-020ME Length: 1 780 mm Width: 530 mm Thickness: 120 mm Must be compatible with item RT24-13-018ME Each Items RT24-12-018ME, RT24-12-019ME and RT24-12-020ME will be considered as a series

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	415
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	MATT 1
	National Stock Number	18-097-1040 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-020ME	See Quantity Awarded	Cover, for mattress To comply with the latest issue of SANS 1291-1, Proof of compliance must be submitted. Cover must be waterproof, removable and non-slip Must be compatible with item RT24-12-019ME Each Items RT24-12-018ME, RT24-12-019ME and RT24-12-020ME will be considered as a series
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	175
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	PTC 4
	National Stock Number	18-177-3429 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-12-021ME	See Quantity Awarded	Trolley, emergency, patient, complete with mattress Variable height , hydraulic, with foot pedal Rising back rest, gas spring assisted X-ray cassette system (for full body length) Trendellenburg and Anti-Trendellenburg mechanism (approximately 12 degrees) Must support a patient of mass 180 kg Oxygen cylinder holder Utility tray Telescopic/adjustable drip rod at head end of trolley Side rails, collapsing Dimensions (approximate): Length: 2 100 mm Width: 750 mm Height: Adjustable from 600 to 900 mm Castors at least 200 mm diameter Centralized braking system with directional lock Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Mattress: Must be in accordance with item RT24-12-022ME Each Items RT24-12-021ME, RT24-12-022ME and RT24-12-023ME shall be considered as a series
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	16888
	Brand Name/Catalogue Number	Hospi-Furn
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-254
	National Stock Number	18-034-9654 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-022ME	See Quantity Awarded	Mattress, for trolley, emergency, patient To comply with the latest issue of SANS 640 and SANS 1291-1, Proof of compliance must be submitted. To be constructed of flexible polyurethane foam, to comply with SANS 640, Grade no. 12, Class 30 Mattress must be radio translucent, waterproof, non-slip or with retaining straps/hooks Cover with waterproof non-slip removable cover as specified in RT24-12-022ME Length: 1 950 mm Width: 600 mm Thickness: 80 mm Must be compatible with item RT24-13-021ME Each Items RT24-12-021ME, RT24-12-022ME and RT24-12-023ME will be considered as a series
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	760
	Brand Name/Catalogue Number	Durafoam
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-102
	National Stock Number	18-097-1041 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-12-023ME	See Quantity Awarded	Cover, for mattress, emergency trolley To comply with the latest issue of SANS 1291-1, Proof of compliance must be submitted. Cover must be removable, waterproof and non-slip Must be compatible with item RT24-13-022ME Each Items RT24-12-021ME, RT24-12-022ME and RT24-12-023ME will be considered as a series
End User	**Response Fields**	**Hospi-Furn (Pty) Ltd**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	435
	Brand Name/Catalogue Number	Durafoam
	Delivery Period (Days)	45
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	n/a
	Supplier Item Number	HF-103
	National Stock Number	18-185-2325 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-027ME	See Quantity Awarded	Trolley, soiled instruments and linen, complete with polyester linen receptacle To comply with specifications on Annexure L, drawing ME 00.30. 03, see attached. Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, Proof of compliance must be submitted. The shelves shall be constructed of 1,2 mm stainless steel sheeting The shelves shall be shaped to fit neatly between the legs of the trolley and be supported on all sides by 15 mm OD tubular rails The shelves shall be free of sharp edges and shall be attached to the rails in a manner to eliminate vibrations between the shelves and the rails. The necessary fittings to achieve this shall be concealed The bottom shelf shall extend all the way to the fifth leg as indicated in drawing ME 00.30.03 of Annexure L and shall be braced by a 15 mm OD transverse member between the other two legs forming a triangle to support the weight of the canvas receptacle Polyester linen receptacle as per RT24-12-028ME The trolley shall be fitted with 75 mm diameter castors. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	1620
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	LIN 51
	National Stock Number	18-021-5056 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-028ME	See Quantity Awarded	Receptacle, polyester linen For instrument/linen trolley Must comply with the relevant sections of subsection 3 of the latest issue of SANS 896 Size: Diameter: 500 mm (± 10mm) Height:: 800 mm (± 10 mm) including 100 mm fold over lip. Must be compatible with soiled instruments and linen trolley (item no. RT24-12-027ME)

End User	Response Fields	NEW HORIZON METALS CC
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	290
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	BP 24
	National Stock Number	18-097-1049 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-029ME	See Quantity Awarded	Trolley, utillity To comply with the latest issue of CKS 242, Type B (fig 2) Material: Stainless steel: To comply with the latest issue of SANS 417, subsecition 4.1.2, Proof of compliance must be submitted. Exception: With loop handles and not stick handles The trolley must have a smooth directional satin finish The trolley shall be fitted with 100 mm diameter castors Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	3950
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	UT 7
	National Stock Number	18-016-3936 EA
	Total Points	99
Item No	**Quantity Required**	**Description**
RT24-12-030ME	See Quantity Awarded	Carrier, soiled linen, with receptacle Polyester linen as per item on RT24-12-031ME To comply with the latest issue of SANS 896, Type A Mild steel with epoxy/nylon powder-coated finish to comply with SANS 778 paragraph 5.2, Proof of compliance must be submitted. Item RT24-12-030ME and RT24-12-031ME will be considered as series Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	805.1
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	SLT 067
	National Stock Number	18-007-6051 EA
	Total Points	99

Item No	Quantity Required	Description
RT24-12-031ME	See Quantity Awarded	Receptacle, polyester linen, for carrier To comply with the latest issue of SANS 896, subsection 3.6 Receptacle to have handles as specified in subsection 3.6.1 The draw cord and eyelets to comply with paragraphs 3.1.6 and 3.1.8 of the latest issue of SANS 896. Must be compatible with soiled linen carrier - item RT24-12-030ME Items RT24-12-030ME and RT24-12-031ME will be considered as a series Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	295
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	POLY 4
	National Stock Number	18-097-1051 EA
	Total Points	97.6687
Item No	**Quantity Required**	**Description**
RT24-12-033ME	See Quantity Awarded	Carrire, soiled linen, plastc box Moulded heavy duty plastic box type Colour of box: WHITE Lockable hinged top/lid Durable nylon/rubber bumper strip around the base of frame Frame with rounded corners Size of Box: Height: 800 mm (± 20mm) Width: 620 mm (± 20mm) Length: 910 mm (±20- mm) Mounted on four heavy duty castors, 75 mm diameter, two swivel and two fixed direction. Castors must comply with the latest issue of SANS 621, proof of compliance must be submitted. Where castors are fitted into steel tubular legs, the tube shall be of wall thickness not less than 2,0mm and castors shall be fixed to the tube by one of the following methods: a. Solid plug (long) complying with SANS 621 subsection 3.5.6 or b. Screwed into 35mm long sleeves welded into the tubular members and locked in an acceptable manner c. Rubber or plastic expanding sleeves for fitting castors are not acceptable Each
End User	**Response Fields**	**NEW HORIZON METALS CC**
As listed in Special Requirements and Conditions	**Responses**	
	Quantity Awarded - 1.0000	1
	Delivered Price	4752
	Brand Name/Catalogue Number	New Horizon
	Delivery Period (Days)	30
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	Each
	Supplier Item Number	LC 910
	National Stock Number	18-097-0813 EA
	Total Points	98.6441

Item No	Quantity Required	Description
RT24-13-001ME	See Quantity Awarded	First-aid kit The entire contents to be contained in a metal or plastic box complying with the following: Dimentions of must permit the adequate storing of the content, with all teh bottles in an upright position. Front of the box must be hinged at the bottom and securely supported by chains (of a type which do not become entangled) on both sides or similiar means to provide a platform to work on when in the horizontal fold down The box must be provided with a suitable devices for securing it to the wall The box must be fitted with a clasp and staple for locking purposes The box is to be finished according to the latest issue of SANS 1188-1 Please see the attached full specification including the minimum contents of first aid kit Each

End User	Response Fields	Ecomed Medical cc
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	523.47
	Brand Name/Catalogue Number	Ultra
	Delivery Period (Days)	56
	Minimum order Quantities	1
	Unit Of Measure	each
	UOM Offered/Spec Deviation	each
	Supplier Item Number	2002-1301
	National Stock Number	18-015-5753 EA
	Total Points	92

Item No	Quantity Required	Description
RT24-13-002ME	See Quantity Awarded	First aid kit, refill Wound cleaner (100 ml) Swabs for cleaning wounds Cotton wool for padding (100 g) Sterile gauze (minimum quantity 10) Absorbent material, 100g One forceps (for splinters) One pair of scissors (minimum size 100 mm) One card safety pins Four triangular bandages Four roller bandages (75 mm x 5 m) Four roller bandages (100 mm x 5 m) One roll elastic adhesive (25 mm x 3 m) One anti allergenic adhesive strip (25 mm x 3 m) One packet adhesive dressing strips (minimum quantity 10 assorted sizes) Four first aid dressings (75 mm x 100 mm) Four first aid dressings (150 mm x 200 mm) Two straight splints Two cardio pulmonary resuscitation mouthpieces or similar device Adjustable cervical collar Two burn shields 10 x 10 cm Antiseptic powder Two pairs latex-free gloves (medium) Two pairs latex-free gloves (large) Disposable, sealable plastic bag

End User	Response Fields	Meddreg Technology
As listed in Special Requirements and Conditions	Responses	
	Quantity Awarded - 1.0000	1
	Delivered Price	292.41
	Brand Name/Catalogue Number	First Aid Refills
	Delivery Period (Days)	10
	Minimum order Quantities	10
	Unit Of Measure	each
	UOM Offered/Spec Deviation	0
	Supplier Item Number	UTM 2001
	National Stock Number	18-187-1259 EA
	Total Points	98